

FILTER HOUSINGS

CARTRIDGE FILTERS

Housings for cartridge filter in AISI 304 (optional AISI 316) material with a fast **V-Band clamp** closure or **swing bolt hinged**. They can accept DOE or 222 cartridge 20" 30" 40" length.

The housings come with ½" vent and drain port and are available in "B7" version with rated pressure of 7 Bar or "B10" with 10 Bar of rated pressure, those last are also available with optional flanged I/O connection as optional

Typical application are Waste water treatment, RO pre filtration, Municipal drinking water, Industrial process application

Flow rate:	15 to 44 m ³ /h – 66 to 196 GPM
Material :	SS AISI 304 (optional AISI 316)
Cartridge suitable :	DOE or 222
Cartridge lenght :	20" - 30" - 40"
Closure cap :	V-Clamp / swing bolt hinged
Working position :	Vertical
Working pressure :	7 bar for B7 version 10 bar for B10 version
I/O connection :	1 ½" or 2" threaded male
Max working pressure :	7 Bar standard
Drain :	½" male
Vent :	½" male



Model	Flow rate		I/O	Dimension/mm	Cartridge
CF340P15	15 m ³ /h	66 GPM	1 ½"	H1300 x D170	3 x 40"
CF520P15	18 m ³ /h	80 GPM	1 ½"	H810 x D200	5 x 20"
CF530P2	25 m ³ /h	110 GPM	2"	H1060 x D200	5 x 30"
CF540P2	34 m ³ /h	150 GPM	2"	H1360 x D200	5 x 40"
CF740P2	44 m ³ /h	196 GPM	2"	H1370 x D250	7 x 40"